

**RYCO 200 INTERCHANGEABLE SERIES**

Interchangeable with Ryco 200 & Jamec 900 Series  
**WILL PASS APPROX 60CFM @ 90PSI**  
 Brass construction with stainless steel internals.  
 NBR o'rings

**One Touch Connection.**

	<b>PART No</b>	<b>SIZE</b>
	06RC200 06RC200S 06RC243 06RC209	1/4 Female 1/4 Female Steel 3/8 Female 1/2 Female
	06RC201 06RC201S 06RC244	1/4 Male 1/4 Male Steel 3/8 Male
	06RC245 06RC240 06RC241 06RC241S 06RC242	1/4 Barb 5/16 Barb 3/8 Barb 3/8 Barb Steel 1/2 Barb

**RYCO 200 SERIES ADAPTORS**

To be used with the Ryco 200 and 290 series couplings and with the IFS interchangeable series.  
 Brass or steel construction.

	<b>PART No</b>	<b>SIZE</b>
	06.R255 06.R203 06.R203S 06.R266 06.R266S 06.R270	1/8 Female 1/4 Female 1/4 Female Steel 3/8 Female 3/8 Female Steel 1/2 Female
	06.R204 06.R202 06.R202S 06.R251 06.R251S 06.R252 06.R252S	1/8 Male 1/4 Male 1/4 Male Steel 3/8 Male 3/8 Male Steel 1/2 Male 1/2 Male Steel
	06.R205 06.R205S 06.R206 06.R206S 06.R206A 06.R206AS 06.R254 06.R254S	1/4 Barb 1/4 Barb Steel 5/16 Barb 5/16 Barb Steel 3/8 Barb 3/8 Barb Steel 1/2 Barb 1/2 Barb Steel

**RYCO 200 SERIES COUPLERS**

**WILL PASS APPROX 45CFM @ 90PSI**  
 Brass or steel construction.

	<b>PART No</b>	<b>SIZE</b>
	06.R200 06.R200S 06.R243 06.R243S	1/4 Female 1/4 Female Steel 3/8 Female 3/8 Female Steel
	06.R201 06.R201S 06.R244 06.R244S	1/4 Male 1/4 Male Steel 3/8 Male 3/8 Male Steel
	06.R245 06.R245S 06.R240 06.R240S 06.R241 06.R241S	1/4 Barb 1/4 Barb Steel 5/16 Barb 5/16 Barb Steel 3/8 Barb 3/8 Barb Steel

**RYCO 290 SERIES COUPLERS**

**WILL PASS APPROX 90CFM @ 90PSI**  
 Plated steel Construction.

	<b>PART No</b>	<b>SIZE</b>
	06.R290 06.R292 06.R294	1/4 Female 3/8 Female 1/2 Female
	06.R291 06.R293 06.R295	1/4 Male 3/8 Male 1/2 Male
	06.R298 06.R299	3/8 Barb 1/2 Barb



Fitted hose assemblies with Ryco and Nitto air couplers available.  
 See Page 76 for details.

## RYCO 500 INTERCHANGEABLE SERIES

Interchangeable with Ryco 500, Cejn 320, Rectus 26 & Jamec Euro Series.

WILL PASS UP TO 70CFM @ 90PSI

Nickel plated steel construction.

	<b>PART No</b>	<b>SIZE</b>
	06RC500 06RC543 06RC546	1/4 Female 3/8 Female 1/2 Female
	06RC501 06RC544 06RC547	1/4 Male 3/8 Male 1/2 Male
	06RC545 06RC540 06RC541 06RC542	1/4 Barb 5/16 Barb 3/8 Barb 1/2 Barb

## RYCO 500 SERIES ADAPTORS

Interchangeable with Ryco 500 Series and Cejn 320 Series

	<b>PART No</b>	<b>SIZE</b>
	06RC503 06RC566 06RC570	1/4 Female 3/8 Female 1/2 Female
	06RC502 06RC551 06RC552	1/4 Male 3/8 Male 1/2 Male
	06RC505 06RC506 06RC506A 06RC554	1/4 Barb 5/16 Barb 3/8 Barb 1/2 Barb

## RYCO 300 SERIES COUPLERS

WILL PASS APPROX 165CFM @ 90PSI  
Steel construction.

	<b>PART No</b>	<b>SIZE</b>
	06.R322 06.R320	3/8 Female 1/2 Female
	06.R323 06.R321	3/8 Male 1/2 Male
	06.R340 06.R341	3/8 Barb 1/2 Barb

## RYCO 300 SERIES ADAPTORS

	<b>PART No</b>	<b>SIZE</b>
	06.R330 06.R303	3/8 Female 1/2 Female
	06.R332 06.R304 06.R302	1/4 Male 3/8 Male 1/2 Male
	06.R305 06.R306	3/8 Barb 1/2 Barb

## TEMA DIVE COUPLERS

The Tema 2500 Series is specially designed for the diving industry.

The coupling comprises of a safety locking ring to prevent accidental uncoupling. The 2520RF adaptor is stainless steel.



	<b>PART No.</b>	<b>SIZE</b>
	T-2510ELRF	1/4 Female
	T-2520RF	1/4 Female

For larger hydraulic Tema couplings refer to Page 29

**NITTO HI COUPLERS**

WILL PASS UP TO 70CFM @ 90PSI.  
 Nickel Plated Steel Construction.  
**Also available in Brass and Stainless Steel.**  
 NBR o'ring for steel couplers

	<b>PART No</b>	<b>SIZE</b>
	20SF	1/4 Female
	30SF	3/8 Female
	40SF	1/2 Female
	20SM	1/4 Male
	30SM	3/8 Male
	40SM	1/2 Male
	20SH	1/4 Barb
	30SH	3/8 Barb
	40SH	1/2 Barb

**NITTO 200 SERIES HI COUPLERS**

WILL PASS UP TO 90CFM @ 90PSI.  
 One touch connection.

	<b>PART No</b>	<b>SIZE</b>
	200-20SF	1/4 Female
	200-30SF	3/8 Female
	200-40SF	1/2 Female
	200-20SM	1/4 Male
	200-30SM	3/8 Male
	200-40SM	1/2 Male
	200-20SH	1/4 Barb
	200-30SH	3/8 Barb
	200-40SH	1/2 Barb

**NITTO ADAPTORS**

Use for both Hi Coupler and the One Touch Coupler.  
 Nickel Plated Steel Construction.  
**Also available in Brass and Stainless Steel.**

	<b>PART No</b>	<b>SIZE</b>
	20PF	1/4 Female
	30PF	3/8 Female
	40PF	1/2 Female
	20PM	1/4 Male
	30PM	3/8 Male
	40PM	1/2 Male
	20PH	1/4 Barb
	30PH	3/8 Barb
	40PH	1/2 Barb

**NITTO INTERCHANGEABLE COUPLERS**

One touch connection.  
 Interchangeable with Nitto Couplers.  
 WILL PASS UP TO 70CFM @ 90PSI.  
**Available in Steel and 304 Stainless Steel.**  
 NBR o'ring for steel couplers  
 Viton o'ring for stainless steel couplers

	<b>PART No</b>	<b>SIZE</b>
	06NC20SF	1/4 Female
	06NC30SF	3/8 Female
	06NC40SF	1/2 Female
	06NC20SM	1/4 Male
	06NC30SM	3/8 Male
	06NC40SM	1/2 Male
	06NC20SH	1/4 Barb
	06NC30SH	3/8 Barb
	06NC40SH	1/2 Barb

**NITTO INTERCHANGEABLE ADAPTORS**

Interchangeable with Nitto Couplers.  
**Available in Steel and 304 Stainless Steel**

	<b>PART No</b>	<b>SIZE</b>
	06NC20PF	1/4 Female
	06NC30PF	3/8 Female
	06NC40PF	1/2 Female
	06NC20PM	1/4 Male
	06NC30PM	3/8 Male
	06NC40PM	1/2 Male
	06NC20PH	1/4 Barb
	06NC30PH	3/8 Barb
	06NC40PH	1/2 Barb

**NITTO ROTARY PLUG**

For connection to pneumatic tools. Fits to tool at a 45° angle.  
 Allows 360° rotation.  
 To be used with Nitto style couplers.

	<b>PART No</b>	<b>SIZE</b>
	20PM-RP	1/4 Male
	30PM-RP	3/8 Male




# NITTO COUPLERS

## NITTO LARGE DIAMETER COUPLERS


WILL PASS UP TO 175CFM @ 90PSI  
Nickel Plated Steel Construction.

Also available in Brass and Stainless Steel

	PART No	SIZE
	N-400SF	1/2 Female
	N-600SF	3/4 Female
	N-800SF	1 Female
	N-400SM	1/2 Male
	N-600SM	3/4 Male
	N-800SM	1 Male
	N-400SH	1/2 Barb
	N-600SH	3/4 Barb
	N-800SH	1 Barb

## NITTO LARGE DIAMETER ADAPTORS



Nickel Plated Steel Construction.  
Also available in Brass and Stainless Steel

	PART No	SIZE
	N-400PF	1/2 Female
	N-600PF	3/4 Female
	N-800PF	1 Female
	N-400PM	1/2 Male
	N-600PM	3/4 Male
	N-800PM	1 Male
	N-400PH	1/2 Barb
	N-600PH	3/4 Barb
	N-800PH	1 Barb

# RECTUS COUPLERS

The **21 Series Rectus** couplings are a smaller profile coupler where space is a premium.

WILL PASS APPROX 22CFM @ 90PSI

	PART No	SIZE
	06REC21C-02F	1/8 Female
	06REC21C-04F	1/4 Female
	06REC21C-02M	1/8 Male
	06REC21C-04M	1/4 Male
	06REC21C-06H	6mm Barb
	06REC21C-08H	8mm Barb
	06REC21A-02F	1/8 Female
	06REC21A-04F	1/4 Female
	06REC21A-02M	1/8 Male
	06REC21A-04M	1/4 Male
	06REC21A-06H	6mm Barb
	06REC21A-08H	8mm Barb

The **23 Series Rectus** couplings are compatible with **ARB equipment**.

Offers high flow performance in a compact coupler.

WILL PASS APPROX 44CFM @ 90PSI

	PART No	SIZE
	06REC23C-04F	1/4 Female
	06REC23C-04M	1/4 Male
	06REC23A-04F	1/4 Female
	06REC23A-04M	1/4 Male



A wide range of Rectus couplings are available.  
Please ask our sales staff for more details

**CEJN 320 SERIES E-SAFE SAFETY COUPLERS**

WILL PASS UP TO 74CFM @ 90PSI  
 A two stage disconnection process . Vents the downstream air before disconnection to prevent blowback.

Complies with safety standards ISO 4414 and European Standard EN 983.

	<b>PART No.</b>	<b>SIZE</b>
	C-320-2202	1/4 Female
	C-320-2204	3/8 Female
	C-320-2205	1/2 Female
	C-320-2152	1/4 Male
	C-320-2154	3/8 Male
	C-320-2155	1/2 Male
	C-320-2002	1/4 Barb
	C-320-2003	5/16 Barb
	C-320-2004	3/8 Barb
	C-320-2005	1/2 Barb
	<b>PART No.</b>	<b>SIZE</b>
	C-320-5202	1/4 Female
	C-320-5204	3/8 Female
	C-320-5205	1/2 Female
	C-320-5152	1/4 Male
	C-320-5154	3/8 Male
	C-320-5155	1/2 Male
	C-320-5002	1/4 Barb
	C-320-5003	5/16 Barb
	C-320-5004	3/8 Barb
	C-320-5005	1/2 Barb

**CEJN 342 SERIES AIR BREATHING COUPLERS**

WILL PASS UP TO 69CFM @ 90PSI  
 Designed for air breathing applications. Prevents accidental disconnection

	<b>PART No.</b>	<b>SIZE</b>
	C-342-1202	1/4 Female
	C-342-1204	3/8 Female
	C-342-1205	1/2 Female
	C-342-1152	1/4 Male
	C-342-1154	3/8 Male
	C-342-1155	1/2 Male
	C-342-1002	1/4 Barb
	C-342-1003	5/16 Barb
	C-342-1004	3/8 Barb
	C-342-1005	1/2 Barb
	<b>PART No.</b>	<b>SIZE</b>
	C-342-5202	1/4 Female
	C-342-5204	3/8 Female
	C-342-5152	1/4 Male
	C-342-5154	3/8 Male
	C-342-5155	1/2 Male
	C-342-5002	1/4 Barb
	C-342-5004	3/8 Barb
	C-342-5005	1/2 Barb



**Industrial Fittings Sales has access to the complete range of Cejn couplings. Contact our sales staff with any enquiries.**

**PLASTIC QUICK CONNECTORS**

Material: Acetal resin, s/steel spring.  
 NBR "O" Ring  
 Working Pressure 200psi  
 Provides excellent resistance to agricultural chemicals such as pesticides and weedicides

	<b>PART No</b>	<b>SIZE</b>		<b>PART No</b>	<b>SIZE</b>
	06AC04F	1/4 Male		06AA04M	1/4 Male
				06AA04F	1/4 Female
				06AAH06	6mm Barb
				06AAH08	8mm Barb
				06AAH10	10mm Barb
				06AAH12	12mm Barb

**JAMEC 310 SERIES COUPLERS**

WILL PASS APPROX 30CFM @ 100PSI

	PART No.	SIZE
	06310F4	1/4 Female
	06310F6	3/8 Female
	06310M2	1/8 Male
	06310M4	1/4 Male
	06310T5	5/16 Barb
	06310T6	3/8 Barb
	06310T8	1/2 Barb

**JAMEC 31 SERIES ADAPTORS**

TO SUIT 310 SERIES AND 320 SERIES COUPLERS

	PART No.	SIZE
	0631F2	1/8 Female
	0631F4	1/4 Female
	0631F4S	1/4 F/Male Steel
	0631F6	3/8 Female
	0631M2	1/8 Male
	0631M2S	1/8 Male Steel
	0631M4	1/4 Male
	0631M4S	1/4 Male Steel
	0631M6	3/8 Male
	0631T3	3/16 Barb
	0631T4	1/4 Barb
	0631T5	5/16 Barb
	0631T6	3/8 Barb
	0631T8	1/2 Barb

**JAMEC 320 SERIES COUPLERS**

WILL PASS APPROX 30CFM @ 100PSI  
TWIN BUTTON OPERATION  
Use 31 Series Adaptors

	PART No.	SIZE
	06320F4	1/4 Female
	06320F6	3/8 Female
	06320M4	1/4 Male
	06320M6	3/8 Male

**JAMEC 330 SERIES COUPLERS**

WILL PASS APPROX 66CFM @ 100PSI

COUPLER	PART No.	SIZE
	06330F4	1/4 Female
	06330F6	3/8 Female
	06330F8	1/2 Female
	06330M4	1/4 Male
	06330M6	3/8 Male
	06330M8	1/2 Male
ADAPTOR		
	0633F4	1/4 Female
	0633F8	1/2 Female
	0633M4	1/4 Male
	0633M6	3/8 Male
	0633M8	1/2 Male
	0633T6	3/8 Barb
	0633T8	1/2 Barb

CATEGORY 6

**SWIVEL FITTINGS**

**M & F SWIVEL LOW PRESSURE**

300PSI  
Brass



PART No	THREAD
06SLP-08	1/2 BSP
06SLP-12	3/4 BSP
06SLP-16	1 BSP

**M & F SWIVEL**

3000PSI - 200deg F  
Brass



PART No	THREAD
06S7480	1/4 NPT
06S7080	3/8 NPT

**5000PSI STAINLESS STEEL**

06S7470	1/4 NPT
06S7044	3/8 NPT

**90deg HOSE REEL SWIVEL**

Brass  
3000PSI  
300deg F  
Viton O-Rings



PART No	THREAD
06S7475	1/2 NPT FEM

**M & F SWIVEL - 1200PSI**

Brass



PART No	THREAD
06S5055	3/8 NPT
06S5088	1/2 NPT

**F & F SWIVEL**

Brass construction  
Stainless steel insert.  
3000PSI  
200deg F



PART No	THREAD
06S7045	3/8 NPT

**90DEG M & F SWIVEL**

Brass  
360deg swivel  
3000PSI  
200deg F  
Buna N O-rings



PART No	THREAD
06S7030	3/8 NPT