

Claw couplings are commonly used for conveying air and water.  
All Type A claw coupling sizes are interchangeable.

Standard Material: Zinc plated Steel or 316 Stainless Steel  
Seal: Nitrile Rubber  
Temperature Range: -29° to 71°C  
Working Pressure : 500psi

**FEMALE COUPLING**

**Steel Couplings**



SIZE	PART No
3/8"	59-CCA38F
1/2"	59-CCA50F
3/4"	59-CCA75F
1"	59-CCA100F

**Stainless Steel Couplings**

SIZE	PART No
3/8"	N/A
1/2"	59-CCASS50F
3/4"	59-CCASS75F
1"	59-CCASS100F

**MALE COUPLING**

**Steel Couplings**



SIZE	PART No
3/8"	59-CCA38M
1/2"	59-CCA50M
3/4"	59-CCA75M
1"	59-CCA100M

**Stainless Steel Couplings**

SIZE	PART No
3/8"	N/A
1/2"	59-CCASS50M
3/4"	59-CCASS75M
1"	59-CCASS100M

**BARB COUPLING**

**Steel Couplings**



SIZE	PART No
3/8"	59-CCA38H
1/2"	59-CCA50H
3/4"	59-CCA75H
1"	59-CCA100H

**Stainless Steel Couplings**

SIZE	PART No
3/8"	N/A
1/2"	59-CCASS50H
3/4"	59-CCASS75H
1"	59-CCASS100H

**DOUBLE BOLT CLAW CLAMP**



SIZE	PART No
1/2"	59-DBCC50
3/4"	59-DBCC75
1"	59-DBCC100

**SAFETY PIN**



**PART No**  
59-CCALP

**NITRILE SEAL**



**PART No**  
59-CCAS

**WHIPCHECKS**

These steel cables prevent hose whip in the case of accidental separation of couplers.  
Suitable for Hose to Hose connection.  
Tool to hose also available.



**BLANKING END**



**PART No**  
59-CCABE

**3-WAY SPLITTER**



**PART No**  
59-CCA3W

PART No	LENGTH	CABLE DIA.
59-WC02-11	11"	1/8
59-WC02-20	20"	1/8
59-WC02-28	28"	1/8
59-WC02-38	38"	1/8
59-WC04-22	22"	1/4
59-WC04-28	28"	1/4
59-WC04-38	38"	1/4



Hose assemblies c/w claw couplings and heavy duty rubber air hose are also available.  
See Page 76