

ISO A SERIES COUPLING

Standard Hydraulic Coupling. Available with a poppet or ball valve.

Add a "B" to the part number for ball valve style.

Carbon Steel

Interchangeable with Faster ANV, Parker 6600, Aeroquip FD56 and Snap-Tite 61.

SIZE	MALE	MAX WORKING PRESSURE	FEMALE
	PART No		PART No
1/4"	52AM04	350 BAR	52AF04
3/8"	52AM06	300 BAR	52AF06
1/2"	52AM08	300 BAR	52AF08
3/4"	52AM12	250 BAR	52AF12
1"	52AM16	230 BAR	52AF16



PLUG and CAPS

SIZE	PLUG	CAP
	PART No	PART No
1/4"	52AP04	52AC04
3/8"	52AP06	52AC06
1/2"	52AP08	52AC08
3/4"	52AP12	52AC12
1"	52AP16	52AC16



ISO B SERIES COUPLING

Designed for the industrial sector and other applications where high pressure or resistance to corrosion is required. Both coupling and adaptor feature a shut off valve.

Interchangeable with Faster H, Parker 60, Aeroquip FD45 and Snap-Tite 72.

Available in Brass, 316 Stainless Steel and Carbon Steel.

SIZE	MALE	MAX WORKING PRESSURE	FEMALE
	BRASS		BRASS
1/4"	52BM04	90 BAR	52BF04
3/8"	52BM06	80 BAR	52BF06
1/2"	52BM08	80 BAR	52BF08
	316 S/STEEL		316 S/STEEL
1/4"	52BM04SS	280 BAR	52BF04SS
3/8"	52BM06SS	260 BAR	52BF06SS
1/2"	52BM08SS	260 BAR	52BF08SS
	CARBON STEEL		CARBON STEEL
1/4"	52BM04CS	350 BAR	52BF04CS
1"	52BM16CS	280 BAR	52BF16CS



Plugs and Caps available for 1/4"

Cap: 52BC04
Plug: 52BP04

DIN SERIES COUPLING

Widely used in agricultural, mobile and industrial applications.

Interchangeable with Faster NV-NS, Parker 4000, Aeroquip FD76 and Snap-Tite 60

SIZE	MALE	MAX WORKING PRESSURE	FEMALE
3/4"	52DINM12	250 BAR	52DINF12
1"	52DINM16	220 BAR	52DINF16



GENUINE TEMA COUPLING

Both coupling and adaptor feature a shut off valve. A safety closing ring prevents accidental disconnection. Large flow rate makes the Tema coupling ideal for elevating machinery. Also used in the Chemical industry, off-shore, deep sea and materials handling

Also available in 316 stainless steel.



SIZE	MALE	MAX WORKING PRESSURE	FEMALE
	PART No		PART No
1/4"	52T2520	280 BAR	52T2510
3/8"	52T3820	250 BAR	52T3810
1/2"	52T5020	250 BAR	52T5010
3/4"	52T7520	250 BAR	52T7510
1"	52T10020	200 BAR	52T10010

Male and female couplings are also available with a pressure eliminator. This dissipates static pressure and allows easier coupling by hand. Please ask our sales staff for more information.

Plugs, Caps and Seal Kits (Nitrile)

SIZE	CAPS	PLUGS	SEAL KIT
	PART No	PART No	PART No
1/4"	52T2526	52T2516	52T2500PSN
3/8"	52T3826	52T3816	52T3800PSN
1/2"	52T5026	52T5016	52T5000PSN
3/4"	52T7526	52T7516	52T7500PSN
1"	52T10026	52T10016	52T10000PSN



The full range of Tema Couplings is Available. Contact our sales staff for details.

TEMA INTERCHANGEABLE COUPLINGS

STUCCHI - Made in Italy



Female Coupler

PART No	DESCRIPTION
52S75F	3/4" Female Coupler
52S100F	1" Female Coupler



Male Adaptor

PART No	DESCRIPTION
52S75M	3/4" Male Adaptor
52S100M	1" Male Adaptor

Plugs, Caps and Seal Kits

SIZE	CAPS	PLUGS	SEAL KIT
	PART No	PART No	PART No
3/4"	52S75C	52S75P	52S75SK
1"	52S100C	52S100P	52S100SK



The full range of Stucchi Hydraulic Couplings is available. Contact our sales staff for details.

CPL SERIES FLAT FACE COUPLING

Both coupling and adaptor feature an internal flat valve system that guarantees a total lack of oil leaks during connection and disconnection.
Interchangeable with Faster 2FFI, Parker FEM, Aeroquip FD89 and Snap-Tite 74.



PORT SIZE	BODY SIZE	MALE	MAX WORKING PRESSURE	FEMALE
		PART No		PART No
3/8"	3/8"	52CPLM06	300 BAR	52CPLF06
1/2"	3/8"	52CPLM08	300 BAR	52CPLF08
3/4"	1/2"	52CPLM12	250 BAR	52CPLF12
1"	3/4"	52CPLM16	250 BAR	52CPLF16

BALL VALVES 2-Way

Made of carbon steel. Designed for the industrial and agricultural industries.

SIZE	PART No	MAX WORKING PRESSURE
1/4"	52V2RH04	500 BAR
3/8"	52V2RH06	500 BAR
1/2"	52V2RH08	500 BAR
3/4"	52V2RH12	500 BAR
1"	52V2RH16	500 BAR



BALL VALVES 3-Way

SIZE	PART No	MAX WORKING PRESSURE
1/4"	52V3RH04	500 BAR
3/8"	52V3RH06	500 BAR
1/2"	52V3RH08	500 BAR
3/4"	52V3RH12	500 BAR
1"	52V3RH16	500 BAR

