

SWIVEL FITTINGS



F & M SWIVEL LOW PRESSURE 300PSI Brass PART No THREAD 06SLP-08 1/2 BSP 06SLP-12 3/4 BSP 06SLP-16 1 BSP 	F & M SWIVEL 3000PSI - 200deg F Brass PART No THREAD 06S7480 1/4 NPT 06S7080 3/8 NPT 5000PSI STAINLESS STEEL 06S7470 1/4 NPT 06S7044 3/8 NPT 	90deg HOSE REEL SWIVEL Brass 3000PSI 300deg F Viton O-Rings PART No THREAD 06S7475 1/2 NPT FEM 
F & M SWIVEL - 1200PSI Brass PART No THREAD 06S5055 3/8 NPT 06S5088 1/2 NPT 	F & F SWIVEL Brass construction Stainless steel insert 3000PSI 200deg F PART No THREAD 06S7045 3/8 NPT 	90DEG F & M SWIVEL Brass 360deg swivel 3000PSI 200deg F Buna N O-rings PART No THREAD 06S7030 3/8 NPT 

CLAW COUPLERS (SL TYPE)

SL TYPE CLAW COUPLINGS

A metal claw coupling with a female threaded end and a male hose barb end.

PART No	SIZE STANDARD
59-CCSL050F	1/2 Female
59-CCSL050H	1/2 Hosebarb
59-CCSL050M	1/2 Male

A metal claw coupling with a female threaded end and a male hose barb end.

59-CCSL075F	3/4 Female
59-CCSL075H	3/4 Hosebarb
59-CCSL075M	3/4 Male

59-CCSL100F	1 Female
59-CCSL100H	1 Hosebarb
59-CCSL100M	1 Male

MEDIUM HEAD

59-CCSL150F	1½ Female
59-CCSL150H	1½ Hosebarb
59-CCSL150M	1½ Male

A metal claw coupling with a female threaded end and a male hose barb end.

59-CCSL200F	2 Female
59-CCSL200H	2 Hosebarb
59-CCSL200M	2 Male

BLANKING END

A metal blanking end fitting with a female threaded end and a male hose barb end.

PART No
59-CCSLBE (3/8 - 1¼)
59-CCSLBEM (1½ - 2 Medium)

3-WAY SPLITTER

A metal 3-way splitter fitting with three female threaded ends and three male hose barb ends.

PART No
59-CCSL3W (3/8 - 1¼)
59-CCSL3WM (1½ - 2 Medium)

NITRILE SEAL



PART No DESCRIPTION

- 59-CCSLS Type SL Claw Coupling Standard Seal(3/8 - 1 1/4)
59-CCSLSM Type SL Claw Coupling Medium Nitrle Seal (1 1/2 & 2)

CLAW COUPLERS (TYPE A)

Claw couplings are commonly used for conveying air and water.

All Type A claw coupling sizes are interchangeable.

Standard Material: Zinc plated Steel or 316 Stainless Steel

Seal: Nitrile Rubber

Temperature Range: -29° to 71°C

Working Pressure : 500psi

FEMALE COUPLING



STEEL COUPLINGS

PART No	SIZE
59-CCA038F	3/8
59-CCA050F	1/2
59-CCA075F	3/4
59-CCA100F	1

STAINLESS STEEL COUPLINGS

PART No	SIZE
N/A	3/8
59-CCASS050F	1/2
59-CCASS075F	3/4
59-CCASS100F	1

MALE COUPLING



STEEL COUPLINGS

PART No	SIZE
59-CCA038M	3/8
59-CCA050M	1/2
59-CCA075M	3/4
59-CCA100M	1

STAINLESS STEEL COUPLINGS

PART No	SIZE
N/A	3/8
59-CCASS050M	1/2
59-CCASS075M	3/4
59-CCASS100M	1

BARB COUPLING



STEEL COUPLINGS

PART No	SIZE
59-CCA038H	3/8
59-CCA050H	1/2
59-CCA075H	3/4
59-CCA100H	1

STAINLESS STEEL COUPLINGS

PART No	SIZE
N/A	3/8
59-CCASS050H	1/2
59-CCASS075H	3/4
59-CCASS100H	1

DOUBLE BOLT CLAW CLAMP



SIZE	PART No
1/2	59-DBCC050
3/4	59-DBCC075
1	59-DBCC100

WHIPCHECKS

These steel cables prevent hose whip in the case of accidental separation of couplers.

Suitable for Hose to Hose connection.

Tool to hose also available.



PART No	LENGTH	CABLE DIAMETER
59-WC02-11	11	1/8
59-WC02-20	20	1/8
59-WC02-28	28	1/8
59-WC02-38	38	1/8
59-WC04-22	22	1/4
59-WC04-28	28	1/4
59-WC04-38	38	1/4



SAFETY PIN

PART No
59-CCALP



NITRILE SEAL

PART No
59-CCAS



BLANKING END

PART No
59-CCABE



3-WAY SPLITTER

PART No
59-CCA3W



Hose assemblies c/w claw couplings and heavy duty rubber air hose are also available.

See Page 74