



PCL MK4 TYRE INFLATOR



Made in Sheffield, England, the PCL Mk4 Tyre Inflator is the benchmark upon which all other tyre inflators are compared to.

- Durable, yet lightweight design (923g)
- New design viewing window gives a 20% increase in field of view
- Tested to over 400,000 cycles at 100% accuracy
- Meets European Standards EC 86/217. Compliant with EN 12645:2014

Each inflator is individually factory tested and comes with a calibration certificate.



Inflation Pressure : 0 - 138psi (960kpa)
 Max Inlet Pressure: 200psi (1380kpa)
 Inflation Flow Rate: 18cfm (500 l/min)

PART No
10TIMK4



Replacement non-sealing hold on chucks also available.

Part No: 10TC-CO1A03

AUTO SERIES INFLATOR and CHUCKS

These Auto tyre chucks and tyre inflator incorporate a new design in connecting the chuck to the tyre valve. Simply push the chuck onto the tyre valve and it will lock on, first time, every time. No cumbersome locking levers required. It is a simple one handed operation.

To remove the chuck, just push on the release button. Much easier to use than the traditional lever style tyre chucks.

10TI6003 3 in 1 AUTO TYRE INFLATOR



- Non sealing tyre inflator
- 3 in 1 Gauge (PSI, Bar and Kpa)
- Max pressure 160psi (1100Kpa)
- Depress trigger half way to deflate
- 1/4bsp port
- Incorporates the new clip on Auto tyre chuck

PART No
10TI6003



10TC307 AUTO CLIP ON CHUCK STRAIGHT - Non Sealing



- Non sealing tyre chuck
- 1/4bsp female port

PART No: 10TC307

10TC308 AUTO CLIP ON CHUCK 90 DEGREE - Non Sealing



- Non sealing tyre chuck
- 90 Degree Swivel
- 1/4bsp female port

PART No: 10TC308

TI201D DIGITAL TYRE INFLATOR



Non Sealing Tyre Inflator
Digital gauge measuring kpa, bar and psi
Max Pressure 220psi - 1500kpa

PART No: 10TI201D

*Price breaks occur
for quantity buys*

TC306 LARGE BORE CLIP ON CHUCK –Non Sealing

For use on earthmoving equipment



PART No	DESCRIPTION
10TC306	Large Bore Clip on Chuck - Non Sealing



TC304 HOLD ON CHUCK - Sealing



PART No	DESCRIPTION
10TC304	Dual Hold On Chuck - Sealing

TC302 PREMIUM DUAL HOLD ON CHUCK - Sealing



PART No	DESCRIPTION
10TC302	Premium Dual Hold On Chuck – Sealing
10TC302NS	Premium Dual Hold On Chuck – Non Sealing

TC303 PREMIUM DUAL CLIP ON CHUCK - Sealing



PART No	DESCRIPTION
10TC303	Premium Dual <u>Clip On</u> Chuck - Sealing

TC300 SINGLE HOLD ON CHUCK -Sealing



PART No	DESCRIPTION
10TC300	Single Hold on Chuck - Sealing

TC301 SINGLE CLIP ON CHUCK -Sealing



PART No	DESCRIPTION
10TC301	Single Clip on Chuck –Sealing

TC3031 1/4 BARB CLIP ON CHUCK -Sealing



PART No	DESCRIPTION
10TC3031	1/4 Barb Clip on Chuck - Sealing

TC305 1/4 FEMALE CLIP ON CHUCK -Sealing



PART No	DESCRIPTION
10TC305	1/4 Female clip on chuck - Sealing

TC305NS 1/4 FEMALE CLIP ON CHUCK –Non Sealing



PART No	DESCRIPTION
10TC305NS	1/4 Female clip on chuck - Non-Sealing

SCHRADER VALVE



PART No	DESCRIPTION
10SCHRADER	1/8bsp Short Tank Valve

AIR COUPLING ADAPTOR TO FEMALE SCHRADER VALVE THREAD



Ryco Style



Nitto Style

PART No	DESCRIPTION
10SCH-RYCO	Ryco Male to Female Schrader Thread
10SCH-NITTO	Nitto Male to Female Schrader Thread

TYRE GAUGE WITH STRAIGHT CHUCK



50mm Face
0-60psi Pressure Range
Housing: Chrome plated Steel
Stem with release button and straight chuck

PART No: 10TG-012

TYRE GAUGE WITH ANGLE CHUCK



50mm Face
0-60psi Pressure Range
Housing: Chrome plated Steel
Stem with release button and angle chuck

PART No: 10TG-032

TRUCK TYRE GAUGE



50mm Face
0-160psi Pressure Range
Housing: Chrome plated Steel
Stem incorporates a release button
NBR Braided Hose
Extension Bar with Dual Chuck

PART No: 10TG-041

PCL PENCIL GAUGE

Pocket tyre pressure gauge with an angled head designed to fit on the tyre at 90°. Incorporates a self adjusting friction device which enables the pressure to be read once the gauge is removed from the tyre valve.
Supplied in a durable protective case.
Pressure Range: 6 - 50psi.

PART No: 10TGP-17



PCL PENCIL GAUGE and TYRE THREAD DEPTH GAUGE KIT

PCL pocket tyre gauge plus tyre depth gauge. Able to measure tread 1-26mm

PART No: 10TGK-15



SPIDER HOSES

TYRE INFLATION HOSE FOR TRUCKS

- Available in 4 legs or 6 legs
- Each hose is 2m in length
- Angle and straight chucks supplied
- 1000kpa (145psi) gauge
- The gauges comes with a rubber protective shroud. This will protect the gauge against accidental damage.

PART No	DESCRIPTION
13-SPIDER4-S	4 Arm Spider c/w Schroud
13-SPIDER6-S	6 Arm Spider c/w Schroud



CATEGORY 13